



**UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460**

**OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION**

January 8, 2018

Kevin Kutcel  
Agent  
New Nautical Coatings Inc.  
4805 49<sup>th</sup> Street  
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Revising the label to add optional marking statements, add CAS No, amend storage and disposal language and to add additional brand name  
Product Name: Monterey Water-Based AntiFouling Coating  
EPA Registration Number: 44891-9  
Application Date: November 10, 2017  
Decision Number: 536304

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

**IF THE LABEL NOTIFICATION ALSO INCLUDES ABNS, ADD THE FOLLOWING:**

The alternate brand name has been added to the product record:

- Monterey

Page 2 of 2  
EPA Reg. No. 44891-9  
Decision No. 536304

If you have any questions, you may contact Zebora Johnson at (703) 308-7080 or via email at [johnson.zebora@epa.gov](mailto:johnson.zebora@epa.gov).

Sincerely,

A handwritten signature in cursive script, appearing to read "Zeno Bain".

Zeno Bain,  
Product Manager, 33  
Regulatory Management Branch 1  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Enclosure: Accepted label

Notes to reviewer are bracketed [ ]

Statements in parenthesis are optional or alternative text ( )

[Delete] Strike Through

**HIGHLIGHTED**

[Brand Names]

**Monterey Water-Based Antifouling Coating**

[Alternative Brand Names]

**(Monterey)**

**NOTIFICATION**

44891-9

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

01/08/2018

**MONTEREY**  
**WATER-BASED Antifouling Coating**

ACTIVE INGREDIENT	
Cuprous Oxide (CAS No. 1317-39-1)...	54.67%
OTHER INGREDIENTS.....	45.33%
TOTAL.....	100.00%
Copper expressed as metallic 51.76%	

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING**

**SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS**

**(LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

**[OPTIONAL MARKETING STATEMENTS:]**

(Inflatable)  
(Hull Mounted Transducer)  
(Transducer)  
(Seahawk)  
(Yacht Finishes)  
(Premium Finishes)  
**(Water-Based)**  
**(Sea Hawk)**  
**(Premium Quality)**  
**(Antifouling Coating)**  
**(Self Polishing)**

(Antifouling Paint)  
(Ablative)  
(Antifouling Bottom Paint)  
(Hand Crafted in America!<sup>SM</sup>)  
(Hand Crafted in the USA)  
(American Owned and Hand Crafted)  
(USA Hand Crafted)  
(Water-Based Antifouling Coatings)  
(Multi Season)  
(Water-Based Coating)  
(California Compliant)  
(USA Hand Crafted)  
(CA VOC Code Compliant)  
(Reduced VOC Formulation)  
(78 grams/liter VOC)  
(Contains 78 grams/liter VOC)  
VOC 78 grams/liter  
(Contains 78 g/l VOC)  
(VOC 78 g/l)  
(78 VOC)

[Optional Graphics]

# PREMIUM QUALITY



[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS PROVIDED THE ABOVE WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



[Above will be used with contents and manufacturer depending on the size]

[Net Contents:] (5-gallon pail 18.927 ), (Gallon 3.785 Liters), (Quart 0.9463 Liters)

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### GENERAL DESCRIPTION

Hard ablative, multi-seasonal, water-based antifoulant. Provides protection against algae, barnacles, annelids, tunicates, bryzoa, hydroids, zebra mussels and other fouling organisms. Monterey is abrasion resistant for scrubbing, trailering and dry storage. Reduces paint buildup. This product may only be used to treat the surfaces of hulls on boats and vessels. This product is intended for both salt and fresh water use. Monterey applies easily and dries quickly. It may be used over old antifouling finishes in good condition. Monterey is an antifouling paint in a high-technology vehicle that withstands frequent trailering, beaching and launching. Monterey should not be used on aluminum without a proper barrier system. Please consult with your Sea Hawk Representative.

### SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

### PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss  
Converter: One Pack  
Copper Content: 58%  
Volume Solids: 44%  $\pm$  2%  
Mix Ratio: One Pack  
Shipping Weight: 21-22 Lbs./Gal.  
Flash Point: N/A

#### [DELETE]

Film Thickness: 5 mils wet equals 2.2 dry per coat

Recommended Coats: 2 on entire hull and 3 at waterline

Theoretical Coverage: 320 Sq. Ft./Gal. @ recommended film thickness

### APPLICATION DETAILS

Method: Brush, roller or spray  
Thinner: Water  
Cleaner: Water

#### Overcoating Interval    Drying Time (Hrs)

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

Consult with your Sea Hawk representative for the system best suited for surfaces to be protected.

### REGULATORY DATA

VOC: 78 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least (50 5°F) (10 1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**New Construction: As yard procedures may vary, consult with your Sea Hawk Representative.**

**APPLICATION:** [DELETE] Apply by brush, roller or spray. Apply 5 mils wet, which will yield 202 mils dry per coat. (Apply at least two coats by brush, roller or spray)

### EQUIPMENT

**Brush:** China Bristle

**Roller:** Solvent Resistant Roller Cover 3/8" pile smooth to medium. Prewash Roller Cover to remove loose fibers prior to use.

**Airless Spray:** Minimum 33:1-2 GPM ratio pump; 0.017"-0.026" orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

**THINNING:** If thinning is necessary, thin up to a maximum of 10% with clean potable water.

**CLEANUP:** Clean all equipment immediately after use with water. It is good practice to periodically flush out

spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.

#### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Keep container closed when not in use. Keep container tight and upright to prevent leakage. Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area.

**Pesticide Disposal:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. (Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations).

#### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING.** Causes substantial but temporary eye injury. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not get in eyes or clothing. Do not breathe vapors or spray mist, or dust or chips from sanding. Avoid contact with skin, eyes or clothing. Wear protective eyewear (goggles, face shield, or safety glasses). While spraying paint or sanding boat surface, wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health, unless air monitoring demonstrates vapor/mist levels are below applicable limits. Wear protective clothing (long-sleeved cotton shirt, long pants and hat) and waterproof gloves. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

#### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

#### FIRST AID

<b>IF IN EYES:</b>	<ul style="list-style-type: none"><li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li><li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li><li>• Call a poison control center or doctor for treatment advice.</li></ul>
<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"><li>• Call poison control center or doctor immediately for treatment advice.</li><li>• Have person sip a glass of water if able to swallow.</li><li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li><li>• Do not give anything by mouth to an unconscious person.</li></ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"><li>• Move person to fresh air.</li><li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"><li>• Take off contaminated clothing.</li><li>• Rinse skin immediately with plenty of water for 15 – 20 minutes.</li><li>• Call a poison control center or doctor for treatment advice.</li></ul>
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada <del>+1-703-527-3887</del> (+1-703-741-5970) CHEMTREC. Account #15570. For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	

**IN CASE OF SPILL OR LEAK:** Ventilate area. Absorb with an inert material and dispose of in accordance with applicable local regulations.

**IN CASE OF FIRE:** Use CO<sub>2</sub>, dry chemical, foam or water spray/fog. Cool closed containers with water.

**E.P.A. Reg. No. 44891-9 / E.P.A. Est. No. 44891-FL-1**